



	AVENTOS HK top	AVENTOS HF	AVENTOS HS	AVENTOS HL	AVENTOS HK	AVENTOS HK-S	AVENTOS HK-XS
<b>Lift mechanism</b>	22K2300 22K2500 22K2700 22K2900	20F2200.N5 20F2500.N5 20F2800.N5	20S1A00.N5 20S1B00.N5 20S1C00.N5 20S1D00.N5 20S1E00.N5 20S1F00.N5 20S1G00.N5 20S1H00.N5 20S1I00.N5	20L2100.N5 20L2300.N5 20L2500.N5 20L2700.N5 20L2900.N5	20K2300.N5 20K2500.N5 20K2700.N5 20K2900.N5	20K2B00.N1 20K2C00.N1 20K2E00.N1	20K1101 20K1301 20K1501
<b>Cover set</b>	22K80000.NA (two colors)	20F8000.NA	20S8000.NA	20L8000.N1	20K8000.NA		
<b>Arm assembly set</b>	Included with the lift mechanism	20F3200.01 20F3500.01 20F3800.01 20F3900.01	20S3500.06	20L3200.06 20L3500.06 20L3800.06 20L3900.06	Included with the lift mechanism	Included with the lift mechanism	Included with the lift mechanism. Does require the use of CLIP top BLUMOTION or COMPACT BLUMOTION hinges
<b>Stabilizer rod</b>			20Q1061UN (round)	20Q1061UA (oval)			<b>Cabinet mounting plates</b>
<b>Connector set</b>			20Q153ZN	20Q153ZA			20K5101, 20K51E1 or 20K5501
<b>Hardware set / Front fixing bracket</b>							<b>Door mounting plates</b>
<b>Wood or wide aluminum</b>	20S4200 or 20S4F01*	78Z5530TA8, 175H3F00*	20S4200 or 20S4F01*	20S4200 or 20S4F01*	20S4200 or 20S4F01*	175H3100 or 175H3F00*	20K4101 or 20K4501*
<b>Narrow aluminum</b>	20S4200A	78Z550ATA6	20S4200A	20S4200A	20S4200A	20K4A00A02	20K4101A
<b>Thin fronts</b>	20S42T1		20S42T1	20S42T1	20S42T1		
<b>Restriction clip</b>	Integrated angle adjustment between 75° and 107°	20F7051 (104°) 20F7011 (83°)			20K7041 (100°) 20K7011 (75°)	20K7A41 (100°) 20K7A11 (75°)	Use hinge angle restriction clip
<b>Template + drill bit</b>	65.1051.02 + DB-5mm ZML.0040.01 ZML.2200	65.1051.02 + DB-5mm ZML.0040.01 65.5030.01 + DB-2.5mm	65.1051.02 + DB-5mm ZML.0040.01	65.1051.02 + DB-5mm ZML.0040.01	65.1051.02 + DB-5mm ZML.0040.01	65.1051.02 + DB-5mm ZML.0040.01	65.1051.02 + DB-5mm ZML.0040.01

\*Mounting plate with bracket for use with large overlay five-piece doors



	AVENTOS HK top	AVENTOS HF	AVENTOS HS	AVENTOS HL	AVENTOS HK	AVENTOS HK-S	AVENTOS HK-XS
Max. inside cabinet width	70-1/2"	70-1/2"	70-1/2"	70-1/2"	70-1/2"	70-1/2"	70-1/2"
Min. inside cabinet width	13-1/2"	13-1/2"	13-1/2"	13-1/2"	13-1/2"	13-1/2"	13-1/2"
Max. inside cabinet height	22-1/2"	40-1/2"	30"	21-5/16" (w/20L3900.06)	22-1/2"	22-1/2"	22-1/2"
Min. inside cabinet height	8-1/2"	17-3/8"	12-5/16"	10-5/16" (w/20L3200.06)	7-9/16"	5-7/8"	7-7/8"
Min. inside cabinet depth	9-1/4"	11"	11"	11"	10-5/16"	6-1/2"	5"
Lift mechanisms	4 options	3 options	9 options	5 options	4 options	3 options	3 options
Arm assembly	included	4 options	1 option	4 options	included	included	included
Hardware kits	2 options	2 options	2 options	2 options	2 options	2 options	2 options
Stabilizer rod	not required	not required	yes	yes	not required	not required	not required
Restriction clips	integrated (adjustable from 75° - 107°)	yes (104° or 83°)	N/A	N/A	yes (100° or 75°)	yes (100° or 75°)	yes (see hinge angle restrictions)
SERVO-DRIVE option	yes	yes	yes	yes	yes		
TIP-ON option	yes				yes	yes	yes

■ \*If wider than 46-1/2" use of 20Q153ZN (HS) or 20Q153ZA (HL) connector rod set is required

Blum templates		Blum drill bits	
Description	Part number	Description	Part number
Universal individual template	65.1051.02	5 mm right hand drill bit	DB-5mm
Universal template	ZML.0040.01		
Platemate	65.5030.01	2.5 mm right hand drill bit	DB-2.5mm
Front marking template	ZML.2200		

■ The information above is intended to be used as a guide only, please refer to AVENTOS brochure (LIT.AVT1000) for exact specifications.