



product
design
award

2010



DESIGN
AWARD
2017



Blum-Awards
www.blum.com/award



CLIP top BLUMOTION hinge 110°

Webcode
ID20006 ◀

for cabinet doors

- Elegant design with small overall dimensions thanks to integrated dampening in the hinge boss
- Integrated BLUMOTION soft-close system for soft and effortless closing action (with deactivation)
- CLIP top with or without closing mechanism (spring)
- Harmonious gap layout thanks to convenient and infinitely variable 3-dimensional adjustment
- Tool-free fast assembly and removal of the door via tried and trusted CLIP mechanism
- Various applications possible thanks to different hinge arms, boss fixings and angled spacers

Product overview

Blum CLIP top BLUMOTION hinge 110°. Hinge for standard applications. 110° opening angle. Closing dampening integrated in the hinge boss; this can be deactivated. Tool-free fast assembly and removal of the door from the cabinet using clip-on assembly method. Third location pin in hinge arm for stable hold of the hinge on the mounting plate.

Finishes available

- a) nickel plated²
- b) Onyx black
- c) BCOR surface protection

Assembly on

- a) horizontal mounting plate
- b) cruciform mounting plate

Optionally with cover caps for hinge arm and boss. Optionally with 86° opening angle stop.

Infinitely variable 3-dimensional adjustment: Height max. ± 3 mm, Side ± 2 mm, Depth adjustment via spiral screw + 3/- 2 mm.

Hinge type

- a) CLIP top BLUMOTION sprung
- b) CLIP top sprung. Optional equipment with soft closing.
- c) CLIP top unsprung. Can be combined with mechanical opening support system TIP-ON.

Equipment options

- ▶ ID20148 TIP-ON for doors



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue