



product
design
award

2010



DESIGN
AWARD
2017



Blum-Awards
www.blum.com/award

CLIP top BLUMOTION hinge 95°

Webcode
ID20008 ◀

for inset or overlay blind corner applications

- Elegant design with small overall dimensions thanks to integrated dampening in the hinge boss
- Integrated BLUMOTION soft-close system for soft and effortless closing action (with deactivation)
- Harmonious gap layout thanks to convenient and infinitely variable 3-dimensional adjustment
- Tool-free fast assembly and removal of the door via tried and trusted CLIP mechanism
- Various applications possible thanks to different hinge arms, boss fixings and angled spacers

Product overview

Blum CLIP top BLUMOTION hinge 95°. Hinge for blind corner applications. 95° opening angle. Closing dampening integrated in the hinge boss; this can be deactivated. Tool-free fast assembly and removal of the door from the cabinet using clip-on assembly method. Third location pin in hinge arm for stable hold of the hinge on the mounting plate.

Finishes available

- a) nickel plated²
- b) Onyx black (only for inset application with integrated BLUMOTION soft-close system)
- c) BCOR surface protection³

Assembly on

- a) horizontal mounting plate²
- b) cruciform mounting plate

Optionally with cover caps for hinge arm and boss.

Infinitely variable 3-dimensional adjustment: Height max.

± 3 mm, Side ± 2.5 mm, Depth ± 1 mm.

Hinge type

- a) inset. CLIP top BLUMOTION sprung.
- b) inset. CLIP top sprung. Optional equipment with soft closing.
- c) inset. CLIP top unsprung. Can be combined with mechanical opening support system TIP-ON.
- d) overlay. CLIP top BLUMOTION.

² not available in China

³ only available in China

Equipment options

- ▶ ID20148 TIP-ON for doors



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue