



product
design
award

2010



Designpreis
Deutschland
2011

NOMINEE



Blum-Awards
www.blum.com/award

CLIP top BLUMOTION hinge 95°

Webcode
ID20009 ◀

for narrow aluminium frame doors

- Integrated BLUMOTION soft-close system for soft and effortless closing action (with deactivation)
- Harmonious gap layout thanks to convenient and infinitely variable 3-dimensional adjustment
- Tool-free fast assembly and removal of the door via tried and trusted CLIP mechanism
- Various applications possible thanks to different hinge arms

Product overview

Blum CLIP top BLUMOTION hinge 95°. Hinge for narrow aluminium frame doors. 95° opening angle. Closing dampening integrated in the hinge boss; this can be deactivated. Tool-free fast assembly and removal of the door from the cabinet using clip-on assembly method. Third location pin in hinge arm for stable hold of the hinge on the mounting plate.

Finishes available

- a) nickel plated
- b) Onyx black (only without integrated BLUMOTION soft-close system)

Assembly on

- a) horizontal mounting plate
- b) cruciform mounting plate

Optionally with cover cap for the hinge arm.

Infinitely variable 3-dimensional adjustment: Height max. ± 3 mm, Side ± 2 mm, Depth adjustment via spiral screw + 3/- 2 mm.

Hinge type

- a) CLIP top BLUMOTION sprung
- b) CLIP top sprung. Optional equipment with soft closing.
- c) CLIP top unsprung. Can be combined with mechanical opening support system TIP-ON.

Equipment options

- ▶ ID20148 TIP-ON for doors



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue

blum