



product
design
award

2010



DESIGN
AWARD
2017



Blum-Awards
www.blum.com/award



CLIP top BLUMOTION angled hinges

Webcode
ID20010 ◀

from + 45° to - 45°

- Elegant design with small overall dimensions thanks to integrated dampening in the hinge boss
- Integrated BLUMOTION soft-close system for soft and effortless closing action (with deactivation)
- Suitable for angled applications from +50° to -50° in combination with angled spacers
- Tool-free fast assembly and removal of the door via tried and trusted CLIP mechanism
- Various applications possible thanks to different hinge arms, boss fixings and angled spacers

Product overview

Blum CLIP top BLUMOTION hinge.

Hinge type

- a) CLIP top BLUMOTION sprung.
- b) CLIP top sprung. Optional equipment with soft closing.
- c) CLIP top unsprung. Can be combined with mechanical opening support system TIP-ON.

Angled hinge

- a) +45° (also in onyx black)
- b) +37°
- c) +30° (also in onyx black)
- d) +20°
- e) +15° (also in onyx black)
- f) ± 5° (with profile door hinge 95°)
- g) -15°
- h) -30°
- i) -45°

Closing dampening integrated in the hinge boss; this can be deactivated. Tool-free fast assembly and removal of the door on the cabinet using clip-on assembly method. Third location pin in hinge arm for stable hold of the hinge on the mounting plate.

Infinitely variable 3-dimensional adjustment: Height max. ± 3 mm, Side ± 1.8 mm, Depth adjustment via a spiral screw ± 2 mm.

Optionally with angled spacers for intermediate angles. Optionally with cover caps for hinge arm.

Assembly on

- a) horizontal mounting plate
- b) cruciform mounting plate

Equipment options

- ▶ ID20148 TIP-ON for doors



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue