



TANDEMBOX antaro, TIP-ON BLUMOTION

Webcode
ID20232 ◀

Drawers, height N (Space requirement 85.5 mm), load bearing class 30 kg

- Drawer for TANDEMBOX antaro
- Opens with a light touch, has a feather-light glide and closes silently and effortlessly – 100% mechanically
- 2.5 mm front gap for optimum function.
- Fast, tool-free assembly of front
- Three-dimensional front adjustment

Product overview

Drawer suitable for Blum TANDEMBOX antaro.

Double walled drawer sides in

- a) Steel in silk white
- b) Steel in white aluminium (RAL9006)

With cover caps for drawer sides. Concealed, guided full extension with low-friction cylindrical rollers. Opens with just a touch, has a feather-light glide and closes softly and effortlessly, 100% mechanically with TIP-ON BLUMOTION technology. It is possible to pull to open and push to close. Recommended for optimum synchronisation function.

Cabinet profiles and drawer sides in nominal length and load bearing class

- a) 400 mm, 30 kg
- b) 450 mm, 30 kg
- c) 500 mm, 30 kg
- d) 550 mm, 30 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with 30 kg total load. Option of combining with side stabiliser. Fast, tool-free assembly of front.

Three-dimensional front adjustment. Optional use with Blum "CABLOXX" locking system (ID20267). Optional use with "SPACE STEP" (ID20285).

Equipment options

- ▶ ID20265 TIP-ON BLUMOTION for TANDEMBOX



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning" www.blum.com/catalogue