







Blum-Awards

www.blum.com/award

CLIP top BLUMOTION wide angle hinge 155°

Webcode ID20272 <

for cabinets with inner pull-outs and much more

- Hinge without door protrusion for overlay application (for cabinets with inner pull-outs or pull-out surrounds)
- Integrated BLUMOTION soft-close system for soft and effortless closing action (with deactivation)
- CLIP top with or without closing mechanism (spring)
- Suitable for special applications, e.g. mitre, notched and large overlay doors
- Harmonious gap layout thanks to convenient and infinitely variable 3-dimensional adjustment
- Tool-free fast assembly and removal of the door via tried and trusted CLIP mechanism

Product overview

Blum CLIP top BLUMOTION wide angle hinge 155°. Hinge without door protrusion enables the implementation of furniture with inner pull-outs or pull-out surrounds. Also suitable for special applications (e.g. mitre/notched/large overlay). 155° opening angle. Integrated soft closing in the hinge arm; can be deactivated. Tool-free fast assembly and removal of the door from the cabinet using clip-on assembly method. Third location pin in hinge arm for stable hold of the hinge on the mounting plate.

Finishes available

- a) nickel plated
- b) Onyx black

Optionally with

- a) 110° opening angle stop
- b) 92° opening angle stop

Optionally with cover cap for the hinge arm.

Infinitely variable 3-dimensional adjustment: Height max.

± 3 mm, Side ± 2 mm, Depth adjustment via spiral screw

+ 3/- 2 mm.

Hinge type

- a) CLIP top BLUMOTION sprung.
- b) CLIP top sprung. Optional equipment with soft closing.
- c) CLIP top unsprung. Can be combined with mechanical opening support system TIP-ON.

Assembly on

- a) horizontal mounting plate
- b) cruciform mounting plate

Equipment options

▶ ID20148 TIP-ON for doors



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning" www.blum.com/catalogue