



reddot design award
winner 2018



DESIGN
AWARD
2018



Blum-Awards
www.blum.com/award



CLIP top BLUMOTION CRISTALLO hinge, angled application

Webcode
ID20277 ◀

- 5° to + 15° for glass and mirror doors

- Adhesion plate is glued on to the front, without glass drilling
- Integrated BLUMOTION soft-close system for soft and effortless closing action (with deactivation)
- CLIP top with or without closing mechanism (spring)
- Harmonious gap layout thanks to convenient and infinitely variable 3-dimensional adjustment
- Tool-free, fast assembly and removal of the door and hinge on the adhesion plate thanks to tried-and-tested CLIP mechanism

Product overview

Blum CLIP top BLUMOTION CRISTALLO hinge.

Finishes available

a) nickel plated²

b) BCOR surface protection³

Angled application for glass and mirror doors

a) -5°

b) +5°

c) +10°

d) +15°

Integrated soft closing in the hinge arm; can be deactivated.

Tool-free fast assembly and removal of the door on the cabinet using clip-on assembly method. Fast tool-free mounting of the hinge on the boss plate using CLIP mechanism. Third location pin in hinge arm for stable hold of the hinge on the mounting plate.

Infinitely variable 3-dimensional adjustment: Height max. ± 3 mm, Side ± 2 mm, Depth adjustment via spiral screw + 3/- 2 mm.

Optionally with cover cap for the hinge arm. Assembly on cruciform mounting plate.

Hinge type

a) CLIP top BLUMOTION sprung.

b) CLIP top sprung. Optional equipment with soft closing.

c) CLIP top unsprung. Can be combined with mechanical opening support system TIP-ON.

² not available in China

³ only available in China

Equipment options

▶ ID20148 TIP-ON for doors



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue