reddot design award
winner 2018

DESIGN AWARD 2018

Blum-Awards
www.blum.com/award

CLIP top BLUMOTION hinge for thin doors, angled application

Webcode
ID20278

- 5° to + 15° for thin doors from 8 to 14 mm

- EXPANDO T fixing system for a variety of front materials
- Front thicknesses from 8 mm to 14 mm
- Integrated BLUMOTION soft-close system for soft and effortless closing action (with deactivation)
- CLIP top with or without closing mechanism (spring)
- Harmonious gap layout thanks to convenient and infinitely variable 3-dimensional adjustment
- Tool-free fast assembly and removal of the door via tried and trusted CLIP mechanism

Product overview

Blum CLIP top BLUMOTION hinge for thin doors.
Angled application for thin doors from 8 to 14 mm
a) -5°
b) +5°
c) +10°
d) +15°
Nickel-plated surface. Integrated soft closing in the hinge arm; can be deactivated. Tool-free fast assembly and removal of the door on the cabinet using clip-on assembly method. Third location pin in hinge arm for stable hold of the hinge on the mounting plate.
Infinitely variable 3-dimensional adjustment: Height max. ± 3 mm, Side ± 2 mm, Depth adjustment via spiral screw + 3/- 2 mm.
Optionally with cover caps for hinge arm. Assembly on cruciform mounting plate.

Hinge type
a) CLIP top BLUMOTION sprung.
b) CLIP top sprung. Optional equipment with soft closing.
c) CLIP top unsprung. Can be combined with mechanical opening support system TIP-ON.
With EXPANDO T fixing system for thin fronts. Optional use with Blum fixing system “EXPANDO T” (ID20279) for thin fronts measuring from 8 mm to 14 mm.

Equipment options

- ID20148 TIP-ON for doors
- ID20279 EXPANDO T – fixing system for thin fronts measuring 8 mm and above

Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under “Planning”
www.blum.com/catalogue