



reddot design award
winner 2018



DESIGN
AWARD
2018



Blum-Awards
www.blum.com/award



CLIP top BLUMOTION hinge for thin doors, angled application

Webcode
ID20278 ◀

- 5° to + 15° for thin doors from 8 to 14 mm

- EXPANDO T fixing system for a variety of front materials
- Front thicknesses from 8 mm to 14 mm
- Integrated BLUMOTION soft-close system for soft and effortless closing action (with deactivation)
- CLIP top with or without closing mechanism (spring)
- Harmonious gap layout thanks to convenient and infinitely variable 3-dimensional adjustment
- Tool-free fast assembly and removal of the door via tried and trusted CLIP mechanism

Product overview

Blum CLIP top BLUMOTION hinge for thin doors.
Angled application for thin doors from 8 to 14 mm

- a) -5°
- b) +5°
- c) +10°
- d) +15°

Nickel-plated surface. Integrated soft closing in the hinge arm; can be deactivated. Tool-free fast assembly and removal of the door on the cabinet using clip-on assembly method. Third location pin in hinge arm for stable hold of the hinge on the mounting plate.

Infinitely variable 3-dimensional adjustment: Height max. ± 3 mm, Side ± 2 mm, Depth adjustment via spiral screw + 3/- 2 mm.

Optionally with cover caps for hinge arm. Assembly on cruciform mounting plate.

Hinge type

- a) CLIP top BLUMOTION sprung.
- b) CLIP top sprung. Optional equipment with soft closing.
- c) CLIP top unsprung. Can be combined with mechanical opening support system TIP-ON.

With EXPANDO T fixing system for thin fronts. Optional use with Blum fixing system "EXPANDO T" (ID20279) for thin fronts measuring from 8 mm to 14 mm.

Equipment options

- ▶ ID20148 TIP-ON for doors
- ▶ ID20279 EXPANDO T – fixing system for thin fronts measuring 8 mm and above



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue