



product
design
award

2010



Blum-Awards
www.blum.com/award

CLIP top BLUMOTION hinge 125°

Webcode
ID20282 ◀

for cabinets with inner pull-outs and much more

- Hinge without door protrusion for overlay application (for cabinets with inner pull-outs or pull-out surrounds)
- Hinge for thick fronts and profile/thick doors
- Integrated BLUMOTION soft-close system for soft and effortless closing action (with deactivation)
- Harmonious gap layout thanks to convenient and infinitely variable 3-dimensional adjustment
- Tool-free fast assembly and removal of the door via tried and trusted CLIP mechanism
- Suitable for special applications, e.g. mitred/notched/large overlay doors

Product overview

Blum CLIP top BLUMOTION hinge 125°. Hinge without door protrusion enables the implementation of furniture with inner pull-outs or pull-out surrounds. 125° opening angle.

Finishes available

- a) nickel plated
- b) Onyx black

Integrated soft closing in the hinge arm; can be deactivated. Tool-free fast assembly and removal of the door on the cabinet using clip-on assembly method. Third location pin in hinge arm for stable hold of the hinge on the mounting plate. Also suitable for special applications (e.g. mitre/notched/large overlay).

Infinitely variable 3-dimensional adjustment: Height max. ± 3 mm, Side ± 2 mm, Depth adjustment via spiral screw + 3/- 2 mm.

Optionally with cover caps for hinge arm. Optionally with 92° opening angle stop.

Assembly on

- a) horizontal mounting plate
- b) cruciform mounting plate



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue