



AVENTOS HKi

Webcode
ID20326 ◀

for stay lifts

- Stay lift fitting integrated in the cabinet side
- Ideal for cabinet heights from 162 to 600 mm in wall cabinets
- Easy opening, variable stop and silent and effortless closing thanks to the integrated BLUMOTION dampening
- Harmonious gap design thanks to convenient 3-dimensional front adjustment
- Also possible as a semi-integrated fitting with thin cover cap
- Suitable for combination with TIP-ON for handle-less fronts

Product overview

Blum AVENTOS HKi for stay lifts. Stay lift fitting fully integrated in the cabinet side with low minimum cabinet depth of 268 mm. For wooden and wide/narrow alu frame fronts. Symmetrical lift mechanism with spring package. Lift system can be stopped in any position using variable lift mechanism strength adjustment. Convenient lift mechanism adjustment from the front. High stability even for wide fronts. Integrated closing dampening. Integrated safety feature prevents the lever from being opened unintentionally. Integrated, variable opening angle stop. Simple, tool-free fast installation of the front using clip-on assembly method. No parts projecting beyond the cabinet side. Can be combined with TIP-ON mechanical motion support system. Removal of the lift mechanism without residue. No hinges required. For cabinet heights from 162 mm to 600 mm.

Convenient three-dimensional front adjustment using Torx screws: Height ± 2 mm, Side ± 2 mm, Depth ± 2 mm.

For semi-integrated application: straightforward, minimalist cover cap made of nylon in light grey, silk white or dark grey

- a) silk white
- b) light grey
- c) dark grey

Equipment options

- ▶ ID20153 TIP-ON for AVENTOS stay lifts



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue