



AVENTOS HF top

Webcode
ID20344 ◀

for bi-fold lift systems

- Ideal for higher wall cabinets with divided fronts
- Easy opening, variable stop, soft and effortless closing with integrated BLUMOTION soft-close system
- Harmonious gap design thanks to convenient 3-dimensional front adjustment
- Fast assembly and removal of the front using CLIP technology
- Suitable for combination with SERVO-DRIVE for handle-less fronts

Product overview

Blum AVENTOS HF top for bi-fold lift systems. Compact bi-fold fitting with a minimum internal cabinet depth of 264 mm. Upper and lower front can be of varying heights. Symmetrical lift mechanism with spring package. Lift system can be stopped in any position using variable lift mechanism strength adjustment. Convenient lift mechanism adjustment from the front. High stability even for wide fronts. Integrated opening and closing dampening. Removable lever arm, can be adjusted to the respective cabinet height. Integrated, variable opening angle stop. Simple, tool-free fast installation of the front using clip-on assembly method. Centre hinge with clip-on mechanism. Lift mechanism can be attached to the cabinet side before assembly. No parts projecting beyond the cabinet side. Wooden, wide/narrow alu frame fronts, wood-glass combinations, asymmetrical fronts, mitred and rebated applications. Can be combined with the electrical motion support system SERVO-DRIVE. For cabinet heights of 490 to 1,200 mm.

For cabinet widths up to 1,800 mm.

3-dimensional adjustment of the lower front: Height ± 2 mm, Side ± 2 mm, Depth $+ 3/- 2$ mm.

3-dimensional adjustment of the overall front: Height ± 2 mm, Side ± 2 mm, Depth $+ 3/- 2$ mm.

Straightforward, minimalist cover cap made of nylon in

- a) silk white
- b) light grey
- c) dark grey

Equipment options

- ▶ ID20140 SERVO-DRIVE for AVENTOS HF top



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue