

AVENTOS HK-S

Minimalist new cover caps

www.blum.com



Memo

i

Available in three colours



Light grey



Silk white



Dark grey

The AVENTOS HK-S stay lift for small fronts has a new look. Its cover caps have been refashioned, creating a minimalist and sleek design to match AVENTOS HK top. The new cover caps come in three colours: light grey, silk white and dark grey. The small stay lift fits stylishly into cabinets of different designs and delivers top quality motion.

Can be combined with AVENTOS HK top

The new design means that AVENTOS HK-S and the new AVENTOS HK top stay lift can easily be combined in the same living area. So you can mix cabinets of different sizes (with stay lifts) to create a harmonious look throughout the home.




AVENTOS HK top with dark grey cover cap

AVENTOS HK-S



The new cover caps

Order specification



Power factor (LF)

Power factor (LF) = cabinet height (KH) [mm] x front weight incl. double handle weight [kg]

We recommend the more powerful lift mechanism for overlapping areas.

Lift mechanism (symmetrical)				
	LF	OW	Standard	TIP-ON
	220–500	107°	1 x 20K2A01.02 + 1 x 20K2C01.02	1 x 20K2A01 + 1 x 20K2C01T
	400–1000	107°	2 x 20K2C01.02	2 x 20K2C01T
	680–1520	107°	1 x 20K2C01.02 + 1 x 20K2E01.02	1 x 20K2C01T + 1 x 20K2E01T
	960–2215	107°	2 x 20K2E01.02	2 x 20K2E01T

Note

The power factor (LF) can be increased by 50% when using a third lift mechanism.
It is not possible to use 2x 20K2A01.02.

2	Cover cap set
	HGR, SW, TGR
	left/right
	2 x 20K8A21.21
Consisting of:	
2a 2 x Cover cap left/right	
2b 2 x Small cover cap, premounted, embossed with Blum logo, in-mold brushed stainless steel	

 	3	Front fixing bracket		
	Fixing method		Spacing (mm)	
	Screw-on version		0	*
	EXPANDO		0	
	Knock-in version		0	
Wooden fronts and wide alu frames				2 x

Horizontal steel mounting plates with 0 mm spacing should be used.

* Use 2 chipboard screws (609.1x00) per side for wooden fronts.
Use 2 counter sunk self-tapping screws (660.0950) per side for wide alu frames.

	Front fixing bracket set		
			
	Narrow alu frames	1 x	20K4A00A02

	4	TIP-ON set	
		For drilling Ø 10 x 50 mm	
		SW, TS, R7036	
		Short version	956.1004
		Up to cabinet height (KH) 600 mm	
Consisting of:			
4a 1 x TIP-ON			
4b 1 x Screw-on catch plate			
1 x Chipboard screw 609.1500			
1 x Comment: glue-on catch plate (alternative to screw-on version)			

	5	Straight adapter plate
		Screws**
		SW, TS, R7036, NI-L
		Short version

Alternative to straight adapter plate

	Cruciform adapter plate		
	Screws**		
	R7036		
	Long version		956A1501

** Assemble using Ø 3.5 mm or Ø 4 mm chipboard screws.

	Opening angle stop (optional)		
	100°, dark grey	2 x	20K7A41
	75°, dust grey	2 x	20K7A11

	Chipboard screw (optional)		
	Countersunk screw, Ø 4		
			664.3500

□ Standard LF Power factor
■ TIP-ON OW Opening angle

HGR= light grey, SW= silk white, TGR= dark grey, TS= terra black,
R7036= RAL 7036 platinum grey, NI-L= nickel-lacquered